

Multitec® 520



Versatile multiple gas warning device for workplace monitoring



Device functionality

The **Multitec® 520** provides the ability to measure six gases simultaneously, meaning that this gas warning device can be used practically anywhere.

A large display allows all parameters to be quickly read from a single screen.

The **Multitec® 520** integrates perfectly into the new family of devices from SEWERIN, ensuring compatibility with the comprehensive range of existing accessories.

Features

Intuitive, menu-driven user interface with jog dial and function keys

Large transflective display, very good readability in direct sunlight

Selective infrared sensors for hydrocarbons and carbon dioxide

Highly durable electro-chemical sensors for oxygen and toxic gases

Power supply via 4 replaceable AA-size rechargeable batteries or disposable batteries

Minimum 8 hour battery life in use, rapid charging in 4 hours

Explosion protection:

TÜV 07 ATEX 553353 X x II2G Ex d e ib IIB T4, IIC when used with TG8 carrying bag

Measuring function: BVS 09 ATEX G 001 X, PFG 08 G 002 X

Results of functional tests stored electronically in device

PC communication via USB port and free software for evaluation of measurement results

Measuring ranges and sensors

Gas type	Measuring range	Sensor type
Methane	0 – 100 % LEL	Infrared sensor
Carbon dioxide	0.0 – 5 % vol.	Infrared sensor
Oxygen	0.0 – 25 % vol.	Electro-chemical sensor
Carbon monoxide	0 – 500 ppm	Electro-chemical sensor
Hydrogen sulphide	0 – 100 ppm	Electro-chemical sensor
Ammonia	0 – 100 ppm	Electro-chemical sensor

Please contact us for a comprehensive quotation, including additional technical specifications and information on accessories.

105837 - 07/09 - Subject to technical changes

